



Laminating and
Finishing **SYSTEMS**

LAMpro Jaguar D30

Heavy-Duty, High Speed, Hot Roll Laminator



LAMpro Jaguar D30

The **LAMpro Jaguar D30** is a versatile duplex hot roll laminator perfect for both high-volume and short-run lamination tasks. This easy-to-operate laminator features a side-lay registration table, for precise feeding. Film is easily loaded from the operator side of the machine, allowing easy access to the mandrels. Each mandrel is also equipped with air shafts for quick film change-overs. The Jaguar features preheat rollers as well as a heated nip roller system, providing increased adhesion to digital prints. It gets up to temperature in 10 minutes or less and can operate at speeds up to 49 feet/minute*. Side slitters trim excess material from the sides of the sheets, with integrated slit /scrap take-up reels, and six banks of cooling fans provide tremendous cooling capability to the laminated web before slitting/cutting. The **LAMpro Jaguar D30** is the perfect investment for printers and trade finishing shops looking to streamline their double-sided lamination and encapsulation processes without compromising on quality or productivity.

Finishing Applications Menus, security applications, credit cards, manuals, passes, tickets, etc.



Specifications



Min. 2" x 6"
Max. 30" W



220-240 V



Up to 49'/min

	LAMpro Jaguar D30
Sheet Size	Min: 2" x 6" Max: 30" W
Speed*	Up to 49'/min (depending on application)
Stock weight*	120-400 gsm (depending on application)
Feeder Capacity	N/A
Max. Roll Diameter	14.9"
Film Type	PETpro, NYpro, POLYpro films
Film Core Size	3"
Warm Up Time	10 minutes
Heating	Infrared heater
Trimming/Sheeter	Auxiliary cutter (Sold Separately)
Side Slitters	Included
Size	83"(L) x 44"(W) x 62"(H)
Weight	2,013 lbs
Electrical	220-240 V, 40A, Single Phase

Skandacor™ is proud to offer legendary equipment that works brilliantly with our lineup of **TRADEpro™** and **SPECIALTYpro™** laminate films.



TRADE
Laminate Films



SPECIALTY
Thermal
Laminate Films

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.

skandacor™ The proactive finish.™

1.888.820.9020
skandacor.com