



Systems and
EQUIPMENT

FINISHpro 4751 AF Max

Digital Die Cutting System



FINISHpro 4751 AF Max

The **FINISHpro 4751 AF Max** streamlines small-batch, multi-order print and packaging with fast, stable, quiet operation and fully automated feed-cut-collect for unattended runs. Configurable with single, double, or double plus graphic heads, it supports EOT, UCT, creasing, kiss-cut, and V-cut tools to tackle diverse materials. Delivering speeds up to 1.8 m/s with ± 0.1 mm accuracy, it reduces turnaround while maintaining quality. Cut up to 45mm with the standard head (20mm with the graphic head), on areas up to 51" x 47" (double head) or 51" x 39" (double + graphic). A conveyor with vacuum retrieval and 17" loading height boosts throughput.

Finishing Applications Sample making, short-run customized production for signage, printing and packaging industries, and more.



Specifications



Max. 47" x 51"



Up to 71"/s



380 V AC 50 Hz

	FINISHpro 4751 AF Max
Sheet size	47" x 51" (max)
Cutting speed	Up to 71"/s (1800 mm/s), depending on application
Cutting Thickness	1,7" (standard head) / 0,78" (graphic head), depending on application
Feeder capacity	17.7"
Cutting area	39" x 51" (double + graphic) / 47" x 51" (double head)
Material	Paper, label stock, card stock, foamboard etc.
Cutting accuracy	± 0.1 mm
Accepted file formats	DXF, PLT, PDF, HPG, HPGL, TSK, BRG, XML, CUT, OXF, ISO, AI, PS, EPS
Tools mountable	2 universal cutting modules applicable with EOT, UCT, Crease, Kiss-cut, V-cut, Router*
Display	PC & Monitor
Media hold	Vacuum / Conveyor
Size	122" x 70.9" x 53.1" (L x W x H)
Electrical	380V

*special cutting mat required



Skandacor™ is on a mission to proactively pursue products, solutions, and services that will advance our clients' brands and returns. Our **pro™** lineup of products and equipment creatively deliver the highest value through only the best in opportunity, quality, and performance.

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.